SETUP	SHEET <b>CIGHT</b>
Name: R/C Car Magazine / Drake & Amezcua	Date: Event:
City: State:	Track: Pro-Line Test Track
Track Indoor Tight Smooth Hard Packed Blue Groov Conditions Outdoor Open Rough Loose/Loamy Dry	/e □ Wet □ Low Bite □ High Bite □ Dusty ◯ Med Bite □ Other
Front Suspension	Ackerman Bump Steer
Toe: <u>+2 deg</u> .	
Ride Height: 28mm	Up Down
Camber:1 deg.	
Caster: 20-deg	
Sway Bar: 2.3mm	
Piston/Oil: #54 piston / 45wt Losi oil	
Spring:	
Limiter/Droop: Use droop screw to adjust shock le	ength
Overall Shock Length: 95mm	
Steering Ackerman: Long	
Bump Steer: Down	
Camber Link:	
Shock Location: #2 / Inside on arm	
Front Diff Fluid: 5000	Notes: Drake recommends going 5wt thicker show
Receiver Battery Type:	oil during extremely high outside temps.
Center Diff Fluid: 7000 Rear Suspension	
Toe: 3-deg	
Anti-Squat:	
Ride Height: 29mm	
Camber: -2 deg	
Rear Hub Spacing:	
Sway Bar: <sup>2.5mm</sup>	
Piston/Oil: #55 / 37.5 Losi oil	
Spring: Green	
Limiter/Droop:Use droop screw to adjust shock le	ength Outside 320 Outside
Overall Shock Length: 106mm	
Camber Link: #4 / B on hub	
Shock Location: #2 / inside on arm	
Rear Diff Fluid: 2000	
Engine	Notes:
Engine: Fuel:	
Glow Plug: Head Clearence:	
Pipe/Header: Gearing:	
Clutch Clutch Shoes and Springs Info	Tires Type Compound Insert
Box stock set up	Front:     Rear:
	Notes: Very high-speed, open track set-up.